



## RGS ATEX SINGLE PHASE VACUUM CLEANERS

### A21<sup>PLUS</sup> MX1.3D

#### TECHNICAL FEATURES:

- > Machine body Ø360m
- > Side channel blower with single phase motor asynchronous marked ATEX EX II 3D
- > Vacuum-meter to check filter efficiency
- > Electric cable 10mt long with industrial plug 2P+earth 16A IP67 marked ATEX
- > Manual filter shaker on side
- > Star filter in polyester class "L" antistatic
- > Quick inlet Ø70mm
- > Relief valve put in as standard
- > Container of 25 lt with handle and castors, in stainless steel
- > Rear castors Ø125mm, front castors Ø100mm with brake, antistatic version
- > Standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 9003 white
- > X2 version with container and filter chamber in stainless steel
- > X3 version completely in stainless steel
- > We recommend the use of suction accessories Ø40mm



**MORE  
POWER**



**MORE  
EFFICIENT**



**MORE  
PROTECTION**

Legend	Unit	A21PMX1.3D	
Tension/Voltage	V	1x 230V/50Hz	
Power	Kw	1.1	→ 1.5
Depression max	mbar	225	
Max air flow	m <sup>3</sup> /h	140	→ 210
Primary filtering surface	m <sup>2</sup>	0,70	→ 1,14
Absolute filtering surface	m <sup>2</sup>	1,20	
Container capacity	L	25	
Product inlet	mm	Ø70	
Noise level	dB(A)	67	
Overall dimensions	cm	47x61x135h	
Weight	kg	60	
Protection	IP	65	
Ex Marking	EX	II3D T135 °C	



Aspiratori industriali  
Vacuum cleaners

Impianti centralizzati  
Centralized systems

Trasportatori pneumatici  
Pneumatic conveyors

Tel. +39.059.986833 – info@rgsimpianti.com  
www.rgsvacuumsystems.com – www.rgsimpianti.com