

## A21MX1.3D, A22MX1.3D



### TECHNICAL FEATURES:

- Machine body Ø360mm
- Side channel blower with single phase motor asynchronous marked ATEX EX II 3D
- Vacuum-meter to check filter efficiency
- Electric cable 10mt long with industrial plug 2P+earth 16A IP67 marked ATEX
- Manual filter shaker on side
- Star filter in polyester class "L" antistatic
- Quick inlet Ø70mm
- Relief valve put in as standard
- Container of 25 lt with handle and castors, in stainless steel
- Rear castors Ø125mm, front castors Ø100mm with brake, antistatic version
- Standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 9003 white
- X2 version with container and filter chamber in stainless steel
- X3 version completely in stainless steel
- We recommend the use of suction accessories Ø40mm

		A21MX1.3D	A22MX1.3D
Tension /Voltage	Volts	1x 230V/50Hz	1x 230V/50Hz
Power	Kw	1.1	1.5
Depression max	mbar	200	200
Max air flow	m³/h	140	200
Primary filtering surface	m²	0,7	1,2
Absolute filtering surface	m²	1,1	1,2
Container capacity	Lt	25	25
Product inlet	mm	Ø70	Ø70
Noise level	dB(A)	65	67
Overall dimensions	Cm	47x61x118h	47x61x135h
Weight	Kg	55	60
Protection	IP	55	65