

A346ECO1.3D - A546KECO1.3D A756KECO1.3D



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous marked ATEX EX II 3D put into a protective housing in the back side of the vacuum cleaner
- Electric cable 10m long with industrial plug 3Ph+earth 16A - IP 67
- Star filter in polyester "L" antistatic
- Manual filter shaker on top of the filter chamber for the filter cleaning
- Container of 100lt
- The container has got castors and lateral handles for the emptying and as an option the kit lifting system to have it up with a fork lift
- Quick inlet Ø70
- Support cable reeler in the back side
- Standard version with container in stainless steel, filter chamber and frame painted Ral 7001 grey
- X2 version with bin and filter chamber in stainless steel
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm
- Relief valve put in as standard

		A346ECO1.3D	A546KECO1.3D	A756KECO1.3D
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/50HZ
Power	Kw	2,6	5.2	5.2
Depression Max	mbar max	300	290	290
Max working depression	mbar	220	230	230
Max air flow	m ³ /h	310	520	520
Primary filter surface	m ²	1,90	1,90	3,40-Ø560
Upstream absolute filter surface	m ²	2,20	2,20	2,20
Downstream absolute filter surface	m ²	NO	NO	NO
Cartridge filter surface	m ²	5	5	5
Container capacity	Lt	100	100	100
Product inlet	mm	Ø70	Ø70	Ø70
Noise level	DbA	74	76	76
Overall dimensions	Cm	65X110X152H	65X110X152H	65X120X175H
Weight	Kg	102	135	170
Protection	IP	55	55	55