

A346EPX1.3D - A546KEPX1.3D



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous marked ATEX EX II 3D put into a protective housing in the back side of the vacuum cleaner, with carter in ABS
- Electric cable 10m long with industrial plug 3Ph+earth 16A - IP 67
- Star filter in polyester "L" antistatic
- Manual filter shaker on top of the filter chamber for the filter cleaning
- container of 65 and 100lt
- For models, version with container of 65l on castors with side handles. In 100 lt models, the container has got castors and lateral handles for the emptying and as an option the kit lifting system to have it up with a fork lift
- Quick inlet Ø70
- Accessories compartment and support for the flex hose in the front side
- Support cable reeler in the back side
- standard version with container in stainless steel, filter chamber and frame painted Ral 7001 grey
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm
- Relief valve put in as standard

		A346/60EPX1.3D	A346EPX1.3D	A546/60KEPX1.3D	A546KEPX1.3D
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/HZ	230-400V/50Hz
Power	Kw	2,6	2.6	5.2	5.2
Depression Max	mbar max	300	300	290	290
Max working depression	mbar	220	220	230	230
Max air flow	m ³ /h	310	310	520	520
Primary filter surface	m ²	1,90	1,90	1,90	1,90
Upstream absolute filter surface	m ²	2,20	2,20	2,20	2,20
Downstream absolute filter surface	m ²	NO	NO	NO	NO
Cartridge filter surface	m ²	5	5	5	5
Container capacity	Lt	65	100	65	100
Product inlet	mm	Ø70	Ø70	Ø70	Ø70
Noise level	DbA	74	74	76	76
Overall dimensions	Cm	63X105X135H	63X105X150H	63X105X135H	63X105X150H
Weight	Kg	115	115	142	142
Protection	IP	55	55	55	55