

A63X1.3GD, A65X1.3GD



TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel blower with single phase motor asynchronous marked ATEX EX II 3GD
- Electric cable 10m long with industrial plug 3 Ph+ earth 16A IP67
- Manual filter shaker on side
- Star filter of polyester cat. "L" antistatic
- Quick inlet Ø70mm
- Container of 65 lt with handle and castors, in stainless steel
- Relief valve put in as standard
- Rear wheels Ø150mm, front wheels Ø125mm with brak , antistatic
- standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 7001 grey
- X2 version with container and filter chamber in stainless steel
- We recommend the use of suction accessories Ø40mm e Ø50mm

		A63X1.3GD	A65X1.3GD
Tension / Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	2.6	5.2
Depression max	mbar max	300	290
Max working depression	mbar	220	220
Max air flow	m ³ /h	320	520
Primary filter surface	m ²	1,90	1,90
Absolute filter surface	m ²	2,20	2,20
Container capacity	Lt	65	65
Product inlet	mm	Ø70	Ø70
Noise level	DbA	75	77
Overall dimensions	Cm	64x73x162h	64x73x162h
Weight	Kg	77	93
Protection	IP	65	65