

## AS1556X.3D, AS356X.3D



### TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase or single phase as option, located at the bottom under the container. Marked ATEX EX II 3D
- Machine body Ø560mm
- Electric cable 10m long with industrial plug 3Ph+ earth 16A IP67
- Nylon filter bag antistatic to collect the product
- Inspection window on the cover to check the filter bag
- Relief valve put in as standard
- Straight inlet Ø70
- Container of 150 l in stainless steel
- Wheels Ø63mm with brake, antistatic version

		AS1556X.3D	AS356X.3D
Tension/ Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	1.5	2.6
Depression max	mbar max	250	300
Max working depression	mbar	200	220
Max air flow	m <sup>3</sup> /h	210	310
Primary filter surface	m <sup>2</sup>	NO	NO
Upstream absolute filter	m <sup>2</sup>	NO	NO
Downstream absolute filter	m <sup>2</sup>	1,3	1,3
Cartridge filter surface	m <sup>2</sup>	NO	NO
Container capacity	Lt	150	150
Product inlet	mm	Ø70	Ø70
Noise level	DbA	70	73
Overall dimensions	Cm	Ø56X116H	Ø56X116H
Weight	Kg	60	72
Protection	IP	55	55