

F230X1.3D, F230X1.3GD



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor three phase or in option single phase, placed into a protective housing marked ATEX EX II 3D, EX II 3GD
- Electric cable 10m long with industrial plug 3Ph+ earth 16A IP67
- Vacuum meter to control the filter efficiency
- Body of the machine Ø360mm
- Manual filter shaker on top
- Star filter of polyester cat. "L" antistatic
- Quick inlet Ø70mm
- Relief valve put in as standard
- Waste bin of 25 l with handles, removable, in stainless steel
- Rear castors Ø125mm, front castors Ø100mm with, antistatic
- Standard version with trolley and filter chamber Ral 9003 white, container in stainless steel
- X2 version with container and filter chamber in stainless steel
- X3 version with container, filter chamber and trolley in stainless steel
- Quick installation of all options

		F230X1.3D F230X1.3GD
Tension /Voltage	Volts	230-400V/50Hz
Power	Kw	1,5
Depression Max	mbar max	300
Working Depression	mbar	200
Max air flow	m ³ /h	210
Primary filter surface	m ²	0,70
Upstream absolute filter	m ²	1.55
Downstream absolute filter	m ²	4,8
Cartridge filter surface	m ²	NO
Container capacity	Lt	25
Product inlet	mm	Ø70
Noise level	DbA	72
Overall dimensions	Cm	40X70X150h
Weight	Kg	90
Protection	IP	55