

F340X1.3D, F340X1.3GD



TECHNICAL FEATURES:

- Side channel blower with three phase asynchronous motor, placed into protective housing marked ATEX EX II 3D, EX II 3GD
- Electric cable 10m long with industrial plug 3Ph+ earth 16A IP 67
- Vacuum-meter to monitor the filter efficiency
- Machine body Ø460mm
- Manual filter shaker on top
- Star filter of polyester cat. "L" antistatic
- Quick inlet Ø70mm
- Relief valve put in as standard
- Dust bin of 48 l. with handles, removable, in stainless steel
- Rear castors Ø125mm, front castors Ø100mm with brake, antistatic
- standard version with trolley and filter chamber Ral 9003 white, container in stainless steel
- X2 version with container and filter chamber in stainless steel
- X3 version with container, filter chamber and trolley in stainless steel
- Easy installation of options and accessories

		F340X1.3D F340X1.3GD
Tension / Voltage	Volts	230-400V/50Hz
Power	Kw	2.6
Max depression	mbar max	300
Max working depression	mbar	220
Max air Flow	m ³ /h	310
Primary filter surface	m ²	1,90
Upstream absolute filter	m ²	2,2
Downstream absolute filter	m ²	4,8
Cartridge filter kit	m ²	5
Container capacity	Lt	48
Product inlet	mm	Ø70
Noise level	DbA	73
Overall dimensions	Cm	50X80X154h
Weight	Kg	120
Protection	IP	55